

Technical specification						
R410A Inverter U-Match Cassette type IDU						
Model				GUD71T/A1-S	GUD100T/A-S	GUD140T/A-S
Electrical Data	Power supply		V-Hz-Ph	220~240-50-1	220~240-50-1	220~240-50-1
	Power input ¹	Cooling	kW	0.055	0.100	0.110
		Heating	kW	0.055	0.100	0.110
	Min/Max Voltage	Min/Max Voltage (V)	V	198/264	198/264	198/264
	Power cord spec	Electrical Conduit Size (Inch)	mm ² xpcs	1×3	1×3	1×3
Sound Pressure Level (SS/H/M/L)*			dB (A)	47/45/41/39	50/48/46/42	51/49/46/42
Sound Power Level (SS/H/M/L)*			dB (A)	57	60	61
Refrigerant	Type		—	R410A	R410A	R410A
Air Flow Volume(rated EXP)			CFM	735/674/559/500	883/853/795/706	1059/1000/883/765
			m ³ /h	1250/1150/950/850	1500/1450/1350/1200	1800/1700/1500/1300
Operation temp		Cooling	°C	≥16	≥16	≥16
		Heating	°C	≤30	≤30	≤30
Drainage Connection Size(Outer Diameter×Wall Thickness)			mm	φ25×1.50	φ25×1.5	φ25×1.5
System Operation Control			—	Wireless remote controller	Wireless remote controller	Wireless remote controller
Dimension	Outline dimension (W×D×H)		mm	840×840×200	840×840×240	840×840×290
	Package dimension (L×W×H)		mm	943×923×245	963×963×325	963×963×379
Weight	Net Weight		kg	23.0	31.0	33.0
	Gross Weight		kg	30.0	38.0	41.0
Panel	Outline dimension (W×D×H)		mm	950×950×52	950×950×52	950×950×52
	Package dimension (W×D×H)		mm	1033×1038×112	1033×1038×112	1033×1038×112
	Net Weight		kg	6	6	6
	Gross Weight		kg	9.5	9.5	9.5