

**Technical Specifications****R410A Inverter Multi-Split (Free-Match) Cassette type IDU**

Model	—	GKH(18)BB-K3DNA3A/I	GKH(24)BC-K3DNA4A/I
Cooling Capacity	kW	4.50	7.10
Heating Capacity	kW	5.00	8.00
Air Flow Volume(SS/H/MH/M/ML/L/SL)	m <sup>3</sup> /h	710/670/590/450	1280/1220/1100/880
Sound Pressure Level (SS/H/MH/M/ML/L/SL)	dB (A)	47/45/41/35	47/45/41/36
Dehumidifying Volume	L/h	1.8	2.5
Rated Voltage	V	220-240	220-240
Rated Frequency	Hz	50	50
Phases	—	1	1
Cross-sectional Area of Power Cable Conductor	mm <sup>2</sup>	0.75	0.75
Recommended Power Cable(Core)	N	4	4
Gas Pipe(to indoor unit)	mm	12	16
Liquid pipe	mm	6	9.52
Connection method	—	Flare Connection	Flare Connection
Drain Connection (outer diameter)	mm	φ25	φ25
Dimension of Outline(WxDxH)	mm	596x596x240	840x840x240
Dimension of Carton Box(LxWxH)	mm	775x735x285	960x960x310
Net Weight	kg	20.0	26.0
Gross Weight	kg	24.0	32.0
Panel Outline Dimension(WxDxH)	mm	670x670x50	950x950x60
Panel Dimension of Carton Box(LxWxH)	mm	760x760x90	1030x1035x118
Panel Net Weight	kg	3.5	7
Panel Gross Weight	kg	5	11