

Technical specifications**R410A Inverter U-Match Floor Ceiling type IDU**

Model			GUD140ZD/A-S	GUD160ZD/A-S	
Electrical Data	Power supply		V-Hz-Ph	220~240-50-1	220~240-50-1
	Power input ¹	Cooling	kW	0.150	0.175
		Heating	kW	0.150	0.175
	Min/Max Voltage	Min/Max Voltage (V)	V	198/264	198/264
Power cord spec	Electrical Conduit Size (Inch)	mm ² xpcs	1x3	1x3	
Sound Pressure Level (SS/H/M/L)*			dB (A)	52/50/48/44	54/53/49/45
Refrigerant	Type	—	R410A	R410A	
Air Flow Volume(rated EXP)			CFM	1295/1177/1059/883	1354/1295/1118/942
			m ³ /h	2200/2000/1800/1500	2300/2200/1900/1600
Operation temp		Cooling	°C	≥16	≥16
		Heating	°C	≤30	≤30
Drainage Connection Size(Outer DiameterxWall Thickness)			mm	φ17×1.50	φ17×1.50
System Operation Control			—	Wireless remote controller	Wireless remote controller
Dimension	Outline dimension (WxDxH)		mm	1570×665×235	1570×665×235
	Package dimension (LxWxH)		mm	1729×770×300	1729×770×300
Weight	Net Weight		kg	40.0	42.0
	Gross Weight		kg	47.0	49.0